



MM-6321

Universal 10000 Hour Compressor Fluid

MM-6321 is formulated to provide complete compatibility with a wide variety of OEM and aftermarket rotary screw compressor lubricants. Flushing is not required to switch to MM-6321; in most cases, it can be added directly on top of the existing compressor oil. Its advanced formulation helps avoid costly lubricant-contamination mistakes and helps streamline product inventory. MM-6321 is also formulated to provide outstanding resistance against wear, rust, corrosion and sludge buildup, and to provide 10,000 hours of service.

ATTRIBUTES

- 10,000-hour oil life at 100°C discharge temperature
- Compatible with most OEM PAG compressor lubricants
- Resists water contamination
- Protects against wear, rust and corrosion
- Non-toxic/non-hazardous

TYPICAL LUBRICANT PROPERTIES

| MM-6321 Grades | 32 | 46 | 68 |
|----------------------------|-----------|-----------|-----------|
| Viscosity cSt @ 40°C | 32 | 46.1 | 67 |
| Viscosity cSt @ 100°C | 5.4 | 6.7 | 8.7 |
| Flash Point °F (°C) | 435 (224) | 450 (232) | 478 (248) |
| Copper Corrosion | 1a | 1a | 1a |
| Rust Test: Distilled Water | Pass | Pass | Pass |
| Rust Test: Salt Water | Pass | Pass | Pass |
| Foam Sequence I, II, III | 0/0/0 | 0/0/0 | 0/0/0 |